




ELIX X	TECHNICAL DATASHEET	Created:	31.01.2024
		Modified:	5.3.2024
TYPE	LB1		
CODE	X-55010-S		



PERFORMANCES

Voltage (V):	0
C20(Ah):	50
Cold Cranking Ampere (A):	380 SAE
Charge Acceptance (A):	5
Plates per Cell (pcs):	10
Pos./ Grid Alloy:	Exp. / Pb-Ca-Sn
Neg./ Grid Alloy:	Exp. / Pb-Ca
Separator:	PE(Enveloped)

WEIGHT & DIMENSIONS (max.)

Battery Weight (kg):	11 (+/-2%)
Lead Weight (kg):	6,180
Length (mm):	208
Width (mm):	175
Height (mm):	175
Total Height (mm) :	175

CONTAINER

Type:	LB1
Hold Down:	B3
H.D.Adapter:	No

COVER

Type:	Flat/Seald -
Polarity:	(-,+) Cell layout
Terminal Adapter:	No
Magic Eye:	Yes 1 Ball
Degassing system	Yes Short side(CT)
Flame Arrestor	Yes 2pcs

PLUGS

Type:	No Vent Sealed
-------	----------------

HANDLE

Type:	1x intergated
-------	---------------

OTHERS

Degassing Tube:	No
-----------------	----