





ELIX X	TECHNICAL DATASHEET	Created:	31.01.2024
		Modified:	5.3.2024
TYPE	D23		
CODE	X-56041-S		



PERFORMANCES

Voltage (V):	0
C20(Ah):	60
Cold Cranking Ampere (A):	500 CCA
Charge Acceptance (A):	6
Plates per Cell (pcs):	10
Pos./ Grid Alloy:	Exp. / Pb-Ca-Sn
Neg./ Grid Alloy:	Exp. / Pb-Ca
Separator:	PE(Enveloped)

WEIGHT & DIMENSIONS (max.)

Battery Weight (kg):	14,4 (+/-2%) with acid
Lead Weight (kg):	7,253
Length (mm):	232
Width (mm):	173
Height (mm):	204
Total Height (mm) :	225

CONTAINER

Type:	D23 Acc. To JIS
Hold Down:	No
H.D.Adapter:	No

COVER

Type:	Double Lid -
Polarity:	(+,-) Cell layout
Terminal Adapter:	No
Magic Eye:	Yes 1 Ball
Degassing system	Short side
Flame Arrestor	Yes 2pcs(filter)

PLUGS

Type:	No Vent Sealed
-------	----------------

HANDLE

Type:	Yes -
-------	-------

OTHERS

Degassing Tube:	No
-----------------	----