



Motorcycle



100% Synthetic Lubricants Moto 4stroke	Code	Package
--	------	---------

Euroil Sportbike 5W-40 SL	JASO MA/MA2	E100102	200 L
			60 L

Full synthetic, API SL, JASO MA/MA2

100% synthetic lubricant latest generation without friction modifiers for 4-stroke motorcycles, "touring", "cross", the league. It offers an excellent protection against debris, wear and oxidation. Minimize air absorption and foaming under the most severe operating conditions. It has very low volatility resulting in thickening and consumption to be reduced to a minimum. Because of its special formulation offers. Excellent protection in transmissions & wet clutch discs in which & even under extreme conditions the density will hardly changed, the viscosity remains constant to ensure a solid lubricating film and optimum engine protection in cold starts.

12x1 L

Euroil Sportbike 5W-50 SL	JASO MA/MA2	E100081	200 L
			60 L

Full synthetic, API SL, JASO MA/MA2

100% synthetic lubricant latest generation without friction modifiers for 4-stroke motorcycles, "touring", "cross", the league. It offers an excellent protection against debris, wear and oxidation. Minimize air absorption and foaming under the most severe operating conditions. It has very low volatility resulting in thickening and consumption to be reduced to a minimum. Because of its special formulation offers. Excellent protection in transmissions & wet clutch discs in which & even under extreme conditions the density will hardly changed, the viscosity remains constant to ensure a solid lubricating film and optimum engine protection in cold starts.

12x1 L

Euroil Sportbike 10W-40 SL	JASO MA/MA2	E100070	200 L
			60 L

Full synthetic, API SL, JASO MA/MA2

100% Synthetic lubricant latest generation without friction modifiers for 4-stroke motorcycles, "touring", "cross", the league. It offers an excellent protection against debris, wear and oxidation. Minimize air absorption and foaming under the most severe operating conditions. It has very low volatility resulting in thickening and consumption to be reduced to a minimum. Because of its special formulation offers. Excellent protection in transmissions & wet clutch discs in which & even under extreme conditions the density will hardly changed, the viscosity remains constant to ensure a solid lubricating film and optimum engine protection in cold starts.

12x1 L

Euroil Sportbike 10W-60 SL	JASO MA/MA2	E100082	200 L
			60 L

Full synthetic, API SL, JASO MA/MA2

100% Synthetic lubricant latest generation without friction modifiers for 4-stroke motorcycles, "touring", "cross", the league. It offers an excellent protection against debris, wear and oxidation. Minimize air absorption and foaming under the most severe operating conditions. It has very low volatility resulting in thickening and consumption to be reduced to a minimum. Because of its special formulation offers. Excellent protection in transmissions & wet clutch discs in which & even under extreme conditions the density will hardly changed, the viscosity remains constant to ensure a solid lubricating film and optimum engine protection in cold starts.

12x1 L

Euroil Sportbike 15W50 SL	JASO MA/MA2	E100183	200 L
			60 L

Full synthetic, API SL, JASO MA/MA2

100% Synthetic lubricant latest generation without friction modifiers for 4-stroke motorcycles, "touring", "cross", the league. It offers an excellent protection against debris, wear and oxidation. Minimize air absorption and foaming under the most severe operating conditions. It has very low volatility resulting in thickening and consumption to be reduced to a minimum. Because of its special formulation offers excellent protection to gearboxes and wet clutch discs which even under extreme conditions, the density hardly changed, the viscosity remains constant to ensure a solid lubricating film and optimum engine protection in cold starts.

12x1 L

100% Synthetic Lubricants Moto 4Vstroke	Code	Package
---	------	---------

Euroil Motorcycle 10W40 SG	JASO MA/MA2	E100097	200 L
			60 L

Synthetic, API SG, JASO MA/MA2

Semi-synthetic lubricant latest generation without friction modifiers 4Vstroke motorcycles "Touring", "Cross" & racing. It offers excellent protection against wear, sludge and oxidation under all conditions. The low variability minimizes the change density and consumption of offering excellent protection to gearboxes and drives liquid complexing & preventing slippage & engagement of the movable parts & even at high loads between the teeth. Applies directly lubricating film providing protection not only during a cold start and at high temperatures.

4X1L

12X1L

Euro! Synra 20W50 SH	E100049	60 L 4x4 L
<u>API SH, JASO MA, JASO MA2</u>		
Semi-synthetic engine oil developed specifically for optimum lubrication of four-stroke Motorcycle Ducati. The balanced additive package, along with carefully selected base oil ensures perfect engine performance under all weather and driving conditions. Ensures a consistent lubrication optimum engine protection under the most demanding conditions. Even in use under high temperatures keeps the volatility and minimizes the appearance of foam.		

Euro! Sport Touring 20W50 SG	JASO MA/MA2	E100043	200 L 60 L 4x4 L 12x1 L
<u>Mineral, API SG, JASO MA/MA2</u>			
Mineral oil without friction modifiers, for 4-year-old "Touring", "Cross" & race bikes. It offers excellent protection against wear, sludge and oxidation under all conditions. The low variability minimizes the change in density and consumption of offering excellent protection gearboxes & discs wet clutch & preventing slippage and the involvement of moving parts still in & high loadings between the teeth. Applies directly lubricating film providing protection at cold start and at high temperatures.			

Synthetic Lubricants For 2 Stroke Engine	Code	Package
---	-------------	----------------

Euro! Super 2T Formax	E128433	60 L 20 L 12x1 L
<u>API TC+ Piaggio Hexagon Jaso FD (Low smoke) Husqvarna 266/Chain saw ISO-L- EGD TISI</u>		
100% Synthetic lubricant latest generation of air-cooled & water-cooled two-stroke engines in race conditions, Cross, in chain saws, jet ski, go-karts, snowmobiles & chainsaws. or as pre-mix in single & unleaded gasoline injection systems. Implements strong lubricant film which remains intact, even & at high temperatures for optimum lubrication and protection of the pistons of the cylinders, and bearings. The detergent properties prevent development residual carbon, maintain clean exhaust and spark plug while protecting the components from rust corrosion & wear. Due to special additives is a low smoke product the smell of which is imperceptible.		

Euro! TTX ProScoot	E128428	200 L 60 L 12x1 L
<u>API TC ISO-L-EGD JASO: FC/FD (Low Smoke)</u>		
Semi-synthetic lubricant for high quality air-cooled & water-cooled two-stroke. Bikes & scooter engines, with or without a spray system. It can easily be mixed with fuel in a homogeneous "pro-mix". Provides optimum lubrication under extreme operating conditions. Prevents the appearance of residues in spark plugs, pistons, intake and exhaust passages, and the rim of the pistons. Prevents wear and corrosion of all vital engine parts and reduces exhaust emissions. Because of the ash with low sulfur content, the risk of pre-ignition or explosion resulting burn piston is minimal.		

Euro! Spartamet TTX	880206	24x50 ml
Lubricant specifically for small two-stroke engines. It has top quality and can be used with a mixing ratio of 1: 100. Always follow the recommendations of the engine manufacturer.		

Mineral Lubricants For 2 Stroke Engine	Code	Package
---	-------------	----------------

Euro! SX 2 Stroke oil	E128400	200 L 60 L 20 L 12x1 L
<u>JASO FB- ISO EGB</u>		
Top lubricant small air-cooled & water-cooled two-stroke engines with or without injection system for motorcycles, scooters, pumps, lawn mowers and small generators. Provides optimum lubrication under extreme operating conditions. Mixed easily with gasoline and prevent the presence of residues in spark plugs. Pistons in import & export channels whilst protecting against wear, corrosion and smoke emission. Due to low ash, the risk of piston burning, pre-ignition or explosion is minimal.		

Euro! Super Outboard TCW-3	E128430	60 L 20 L 6x1 L
<u>NMMA:TCW-3 TD; CEC-TSC-4;</u>		
Top lubricant small air-cooled & water-cooled two-stroke engines with or without injection system for motorcycles, scooters, pumps, lawn mowers and small generators. Provides optimum lubrication under extreme operating conditions. Mixed easily with gasoline and prevent the presence of residues in spark plugs. Pistons in import & export channels whilst protecting against wear, corrosion and smoke emission. Due to low ash, the risk of piston burning, pre-ignition or explosion is minimal.		

Fork Oil	Code	Package
----------	------	---------

EuroI M.U. Frontfork Oil 1030

Designed carefully selected **paraffinic base oils with low flow and high viscosity index**. Effective additives ensure excellent hydraulic flexibility, cushioning and smooth motion. scraping, corrosion and foam concentration wear minimized. He has high thermal and oxidative stability and may be applied to a wide range of temperatures. Because of the improvement of stabilizing the viscosity index, the viscosity will remain stable for a very long time.

E107095

6x1 L

EuroI Frontfork SAE 5

Designed carefully selected **paraffinic base oils with low flow and high viscosity index**. Effective additives ensure excellent hydraulic flexibility, cushioning and smooth motion. scraping, corrosion and foam concentration wear minimized. He has high thermal and oxidative stability and may be applied to a wide range of temperatures. Because of the improvement of stabilizing the viscosity index, the viscosity will remain stable for a very long time.

E107980

6x1 L

EuroI Frontfork SAE 10

Designed carefully selected **paraffinic base oils with low flow and high viscosity index**. Effective additives ensure excellent hydraulic flexibility, cushioning and smooth motion. scraping, corrosion and foam concentration wear minimized. He has high thermal and oxidative stability and may be applied to a wide range of temperatures. Because of the improvement of stabilizing the viscosity index, the viscosity will remain stable for a very long time.

E107100

6x1 L

EuroI Frontfork SAE 15

Designed carefully selected **paraffinic base oils with low flow and high viscosity index**. Effective additives ensure excellent hydraulic flexibility, cushioning and smooth motion. scraping, corrosion and foam concentration wear minimized. He has high thermal and oxidative stability and may be applied to a wide range of temperatures. Because of the improvement of stabilizing the viscosity index, the viscosity will remain stable for a very long time.

E107010

6x1 L

EuroI Frontfork SAE 20

Designed carefully selected **paraffinic base oils with low flow and high viscosity index**. Effective additives ensure excellent hydraulic flexibility, cushioning and smooth motion. scraping, corrosion and foam concentration wear minimized. He has high thermal and oxidative stability and may be applied to a wide range of temperatures. Because of the improvement of stabilizing the viscosity index, the viscosity will remain stable for a very long time.

E107020

6x1 L

Brake Fluids	Code	Package
--------------	------	---------

EuroI Brakefluid DOT 4

SAE J1703, ISO 4925, FMVSS 116, BMW 9368, MAN TUC v3681-VW 3057

Synthetic, Visc. -40°C 1100

Boiling temperature 267 ° C

High performance product, designed for hydraulic brake systems for passenger, professional, forklift trucks, scooters, scooter & motorcycle drum or Disc (with or without ABS / ASR). Provides protection against rust, wear and offers optimum reception & heat transfer, and will remain stable not causing residues and non-impacting sealing materials, or metals. Due to the low viscosity, the product guarantees excellent performance under cold climate conditions, but the high point & boiling result, safety and reliability of the braking system to increase significantly. Shall in no case be applied in braking systems of mineral lubricant base (LHM usually green) but & in braking systems silicone based lubricant (purple color, referred to as a DOT 5).

E801400

200 L

20 L

2x5 L

12x1 L

12x500 ml

12x250 ml

EuroI Brakefluid DOT 5.1

SAE J1703, ISO 4925, FMVSS 116

Synthetic, Visc. -40°C 875

Boiling temperature 274°C

Brake fluid silicone-based. It has a wide temperature range (-40 ° C to 260 ° C) & best performance at low temperatures and low toxicity. Helps prevent corrosion and provides excellent lubrication sealing materials & metals. Extends the life cycle of the braking system and does not affect the colors. It can be safely used in hydraulic brake and clutch systems of cars, **Harley Davidson**, racing motorcycles, bicycles, go-karts. Note: The old brake fluid should be drained completely before refilling.

E801500

200 L

60 L

2x5 L

12x1 L

6x250 ml

Spray	Code	Package
Eurol Chain Spray PTFE CHAIN It has been developed for continuous lubrication with deep penetrating action. Special additives and synthetic components provide unique lubrication of all chains (o-rings or other). There dried, keeps the chain flexible and can withstand high temperatures.	E701310	12x400 ml
Eurol Silicone Spray It offers unique lubrication, keeping chains, derailleurs, hinges. Locks & tires running smooth. It repellent properties against dirt, making the surface to be applied waterproofing prevents from melting, corrosion and drying of rubber. The product does not contain acid.	E701320	12x400 ml
Eurol Super Brakecleaner Spray It is a special spray for a quick and effective degreasing and cleaning of brakes, spark plugs, brake linings, disc brakes, engine parts, contact points, chains & metals. There must be cleaned plastic with this product.	E701440	12x500 ml
Eurol Super Lube MD 50 Spray It penetrates deeply, protects metals, makes sticky parts operate smoothly & plastics to look like new. Removes oil, grease, tar and adhesives. Prevents moisture from penetrating segments ignition distributors & Spark.	E701325	12x400 ml
Eurol White grease with PTFE Designed by high performance lithium grease, improved with PTFE. Provides lasting lubrication chains, hinges, springs, bearings, shafts and other moving parts. Gives high heat resistance and corrosion.	E701420	12x400 ml
Eurol Leather Spray It makes the skin soft, flexible and waterproof. Prior to application, the skin should be thoroughly cleaned. Spray from a distance of about 30 cm. After drying, a second layer is applied for enhanced effect.	E701400	12x400 ml
Eurol Penetrating Spray Loosens rusted parts quickly, thanks to the deep penetrating properties. contains disulfide lead for lubrication. Furthermore, active inhibitors contain corrosion resistance.	E701300	12x400 ml

Cleaning Hand Creams	Code	Package
Eurol White Cream >90% biodegradation capacity 4,5 kg Cleaner high quality hands-free solvents, with excellent performance remediation of skin. Because of the neutral PH of the product, prevent skin irritation. prepared by Jojoba esters, aloe extract, lanolin derivatives and with environmentally friendly abrasive (polymer base). It is dermatologically tested and biodegradable. Suitable for removing grease, brake fluid, fuel.	E601440	60 kg 4,5 kg 12x600 ml
Eurol Yellow Cream > 90% biodegradation capacity Active Hand cleanser in gel form , to remove the most stubborn dirt from spray dyeing & printing activities, etc. Contains terpenes, which are known for strong possibility their cleaning, with a pleasant, fresh scent. A fine abrasive (polymer base) makes the product softer hands. It should be applied to dry hands in limited quantities. Rub until weakening dirt, rinse with water and dry with a clean towel. If no water is available, the dirt can also be removed with a dry cloth.	E601430	60 kg 4,5 kg 12x600 ml

Degreasers

Code

Package

Eurol Degreaser Plus HF

330111

20 L

340110

5 L

Has been shaped by strong active emulsifiers and solvents with low loss exhaust. Recommended for rapid degreasing of new cars, cleaning car parts, filters, equipment, engine and tank floor. Can be used for cleaning and grease on floors and walls & will not leave oily layer after washing with water. To be used undiluted, has a pleasant smell and is economical. plastic and Tyres will not be affected during brief contact. It is also safe on all surfaces, as the product has a neutral pH and is biodegradable. The flash point > 61 °C, not classified ADR & does not follow the PGS-15 directive for storage of dangerous goods.

Cleaners

Code

Package

Eurol Brake Cleaner

E302520

5 L

Brake Cleaner chlorine free, fast drying for quick & effective degreasing in cleaning brakes, brake shoes, brake disc, the clutch parts in the engine block, etc. Prevents squeaking brakes. It can also be used for a quick and simple cleaning of electrical and magnetic contacts (interruptor & plugs) as & other parties. Removes easily grease, silicone, asbestos and oil disc brakes & from engine parts. There must be cleaned plastic with this product.

Coolants

Code

Package

Eurol Coolant -26° C Blue

E504100

200 L

It has been developed specifically for open and closed cooling systems, according to modern European car manufacturers (standard BS 6580). It can be used for & heat & central heating installations transport systems. Prevents the formation of extensive erosion, accumulation of foam formation mud. Does not affect rubber, plastics, metals, aluminum or their alloys. Provides a permanent, guaranteed protection from freezing to -26 °C & should be used undiluted. Do not fill with water. Free amines, nitrites, and phosphates.

60 L

20 L

4x5 L

12x1 L

Eurol Coolant G12+ -36° C

E504144

200 L

complies with VW TL-VW 774 D(G12), TL-VW 774 F (G12+), Renault Type D, BS 6580, JASO M325

ASTM D3306/D4656/D4985, NATO S-759

It is developed based on ethylene glycol especially for the new generation cooling systems modern car engines. Prevents the salt concentration and offers excellent protection against cavitation. Furthermore, protects all metals against corrosion, particularly aluminum irons & Alloys, & even at high temperatures. Protect from freezing to -36 °C & contains environmentally friendly additives. This technology is known under name CAT (Organic-Acid-Technology). Should be used without dilution, & Never fill clean water. Shelf-life is 5 years or 650.000 km truck or 250,000 km for passenger cars. prepared without nitrites, amines, boron, phosphorus, and silicon nitrate. The product is compatible with traditional antifreezes.

60 L

20 L

4x5 L

12x1 L

Eurol Coolant G12+ -26° C

E504145

20 L

complies with VW TL-VW 774 D(G12), TL-VW 774 F (G12+), Renault Type D, BS 6580, JASO M325

ASTM D3306/D4656/D4985, NATO S-759

It is developed based on ethylene glycol especially for the new generation cooling systems modern car engines. Prevents the salt concentration and offers excellent protection against cavitation. Furthermore, protects all metals against corrosion, particularly aluminum irons & Alloys, & even at high temperatures. Protect from freezing to -36 °C & contains environmentally friendly additives. This technology is known under name CAT (Organic-Acid-Technology). Should be used without dilution, & Never fill clean water. Shelf-life is 5 years or 650.000 km truck or 250,000 km for passenger cars. prepared without nitrites, amines, boron, phosphorus, and

EuroL Coolant -36° XL Yellow	E504140	200 L
<u>complies with VW TL-VW 774 D (G12), TL-VW 774 F (G12+)</u>		60 L
<u>MB 325.3; Detroit Diesel (incl Powercool plus); Ford WSS-M97B44-D</u>		20 L
<u>Opel-GM6277M +B0401065; MAN 324 Typ SNF; Renault Type D; PSA</u>		4x5 L
<u>Deutz / MWM 0199-99-1115 and 0199-99-2091; BS 6580; ASTM</u>		12x1 L

Coolant long new generation, based on mono-ethylene glycol and organic inhibitors corrosion (without silicate). This special technology can be mixed with antifreeze party, without the risk of accumulation of mud and reduction of antifreeze features. Prevents the formation of scale and offers a excellent protection against cavitation. Moreover, it protects the metal parts in the cooling system against corrosion. It is not without nitrite & amines, boron, phosphorus, silicon and nitric acid and thus, contributes to a cleaner environment. Absolutely safe for rubber, plastics, metals and aluminum or alloys. Modern antifreeze for water-cooled internal combustion engine and protects the system from freezing up to -36 °C. To be used without araisi. O life time of the product is 5 years or 650,000 khm truck or 250,000 khm for passenger cars.

Greases	Code	Package
----------------	-------------	----------------

EuroL BlueStar grease EP 2	E901304	180 kg
<u>NLGI: 2; DIN 51825: KP 2 N-30; ISO-L-XCDIB 2, -35/+150°C</u>		50 kg
It has been developed to follow the continuing technical progress and the requirements of both in the transport sector, as in the industrial sector and for application in bearings, hubs Trailer & chassis parts. Used in bearing wheels & bearings operating under high loads or vibrations at both high (temporarily to 200 ° C) as & at low temperatures while maintaining its coherence. It has an excellent thermal stability & good Membership. The characterizing anticorrosive properties (and in the presence of water), excellent protection antiwear & resistant to water leaching, resulting in a very long life. It has good pumpability over a wide temperature range & offers excellent oxidation stability. Not everybody chemical reaction phenomena with sealing materials.		15 kg
		12x400 g

EuroL Lithium Complex EP2 Plus	E901300	180 kg
<u>NLGI: 2/3, DIN 51825: KP 2 N-30, ISO-L-XBDIB 2-3, -30/+150°C</u>		50 kg
It has been developed to follow the continuing technical progress and the requirements of both in the transport sector, as in the industrial sector and for application in bearings, hubs, Trailer & chassis parts. Used in bearing wheels & bearings operating under high loads or vibrations at both high (temporarily to 200 ° C) as & at low temperatures while maintaining its coherence. It has an excellent thermal stability & good Membership. The characterizing anticorrosive properties (and in the presence of water), excellent protection antiwear & resistant to water leaching, resulting in a very long life. It has good pumpability over a wide temperature range & offers excellent oxidation stability. Not everybody chemical reaction phenomena with sealing materials.		20 kg
		6x600 g
		12x400 g

EuroL Universal Lithium EP 2	E901030	180 kg
<u>NLGI: 2, DIN KP 2,5 N -25, ISO-L-XBCEB 2-3, -25/+130°C</u>		50 kg
High performance grease for all uses with additional EP (without heavy metals) & good pumpability. It offers excellent protection against corrosion and has very good antioxidantg property. It is extremely suitable for high temperature working conditions, heavy loads, shock loads, where water and dirt can penetrate into the lubrication point. Guarantees optimum protection, under adverse working conditions, extending equipment life and reduced maintenance costs. Recommended for application in hot / tropical conditions and reducing maintenance costs.		20 kg
		6x600 g
		12x400 g

EuroL Molybdenum Disulphide MoS2	E901070	50 kg
<u>DIN KF 2 K-30-ISO-L-XCCIB 2-NLGI: 2, -25/+130°C</u>		20 kg
Multipurpose grease based on mineral base oils, lithium soap thickener & Molybdenum disulphide, which forms a chemical reaction with metal surfaces which reduces friction (boundary lubrication) to a minimum. It offers good resistance to oxidation and corrosion and is water repellent. Moreover, it has a good mechanical stability, resulting in very long service life. recommended for the lubrication of heavily loaded bearings, chassis lubrication points, earthmoving and agricultural machinery, CV Joints & semiaxles.		6x600 g

EuroL Ball Bearing Grease EP 2	E901210	180 kg
<u>DIN KP2K-30-ISO-L-XCCEB 2-NLGI:2 -25/+130°C</u>		50 kg
Specially designed for the lubrication of ball bearings. It is water repellent And offers good resistance against oxidation. It has excellent sealing capabilities, engineering stability and adhesion while reducing wear to a minimum, protecting everything from corrosion.		20 kg
		6x600 g

Eurol Lithiumgrease EP 0

E901020

20 kg

DIN KP 0 G -25-ISO-L-XCBEB 0-NLGI: 0 -25/+100°C

High performance lubricant additives EP. It is developed for trucks & buses, equipped with a central lubrication system (with the exception of Willy Vogel). Can be used in gearboxes for which recommended grease NLGI-0. It is semi-fluid and homogeneous structure, facility offering pumping for remote lubrication and at low temperatures. It offers excellent protection against corrosion, oxidation resistance and wash water. It has extreme pressure properties, providing protection from vibration and high loads without losing life.

Eurol Lithiumgrease EP 00

E901010

180 kg

50 kg

20 kg

5 kg

DIN KP 0 G -35-ISO-L-XCBEB 00-NLGI: 00, -35/+100°C

High performance lubricant additives EP. It has been developed specifically for trucks and buses, equipped with central lubrication system "Willy Vogel". It is semi-fluid and has a homogeneous structure offering good pumpability. It has good anti-corrosive and anti-oxidant properties & stable performance at high pressures, making it suitable for operation of heavy vibration.